FTRT-66G


60 MAGICLOTUS GAS GRDDLE - TOP



Gas Fry-top grooved griddle, plate cm.59,5x45 - 2 cooking areas



Construction - Fabricated using CrNi 18/10 AISI 304 grade Stainless Steel Scotch-Brite Satin polish Finish, incorporating 2,5mm thick worktop, rounded edges, chromed details and rear splash back. Knobs with waterproof grades IPX5. Model - Professional Gas Griddle, Smooth, Ribbed or 50 / 50, Normal or Chrome. Normal Plate in FE430B Steel and Chrome in FE510C Steel. High durability and rapid heat up. Burners with Piezoelectric ignition and pilot light, 50 - 300degC control, thermostatic and thermocouple safety valves, Removable liquid containers. Maintenance - All serviceable parts are accessible by the easy removal of front control panel. Fittings - Appliance is supplied with both LPG and Natural Gas conversion jets and adjustable feet.













FTRT-66G

60 MAGICLOTUS GAS GRDDLE - TOP







A Data plate C Gas connection	ISO 7-1 1/2" M
-------------------------------	----------------

MODEL: FTRT-66G

DIMENSIONS: cm. 60x 60x 28h
GAS POWER: 9 kW / 7.740 kcal/h

GAS TYPE: Natural Gas / LPG



kg: 65 m³: 0.283 mm: 630x690x650



